

- A. smooth, clear wood siding is the recommended and preferred siding material. Other siding materials that are designed to mimic wood siding with like design, dimension profile and texture will be considered as they become available. The use of vinyl and/or aluminum siding and trim material or other siding and trim material with faux wood grain or other characteristics that do not mimic wood are not permitted in the District.
- B. wall shingles original to the building may be replaced. If replacement is necessary, the new shingles should match the original in design, dimension profile and texture (this includes decorative wood shingles of Victorian buildings as well as wood or asphalt shingles of Craftsman houses).
- C. should not be concealed beneath artificial or synthetic siding. The application of materials such as vinyl or aluminum over wood siding is not appropriate and their use is prohibited.
- D. the removal of synthetic sidings such as aluminum, asbestos, and vinyl and the restoration of the original wood siding is highly encouraged.
- E. siding exposure must match the original siding exposure. If no original siding exists then a four (4) inch exposure is appropriate or the correct exposure for the architectural style of the structure.

30. SIGNS


Signage in the Historic District include signs for commercial buildings along the northern edge of the District, and governmental, institutional, and office uses. Signs are typically located in front yards about five to ten feet from the public sidewalk. Predominant sign materials are wood and metal.

- A. should be in conformance with Village of Barrington Zoning Ordinance Chapter 4, Part IV “Signs”.
- B. should be kept to minimum with preferably a maximum of two per commercial business or church.
- C. for churches may be freestanding or attached to the face of the building. For commercial buildings signs may be projecting, on windows, or affixed to the face of the building.
- D. should not cover or obscure architectural features, should be unobtrusive as possible and should be of materials compatible with the structure.
- E. should not be illuminated with visible bulbs or luminous paints, but with remote sources.
- F. should be of traditional materials such as finished wood, painted metal, brass, or bronze. Plywood, plastic, or unfinished wood are not permitted.
- G. type and lettering should reflect the 19th and early 20th century character of the District.
- H. should have no more than three colors and use colors that coordinate with the building colors.
- I. for mounting on masonry walls should be anchored into the mortar, not the masonry.

- J. exceeding a dimension of two feet by three feet are discouraged, except for institutional uses, which may have a larger area.

SIGNS: Illustrations

Appropriate Historic Signs




31. SKYLIGHTS


The addition of skylights can make the use of upper floor space or attic space more practical. The installation of skylights is appropriate as long as they are placed on rear roof lines, behind gables or dormers, or otherwise not visible from the street. Skylights that are flush with the roofline or lay flat are appropriate, those with convex or "bubble" designs are not appropriate.

- A. are permitted on rear roof section where not visible from the street.
- B. should be flat or flush with the roofline, not convex or "bubble" designs.

SKYLIGHTS: Illustrations



Appropriate Flat Skylight



Inappropriate "Bubble" Skylight